



PREFERRED
Recycling Equipment Inc.

EPS Compactor C100

EPS compacted up to a 50:1 ratio

- Saving: Save cost and space by compressing your EPS reducing waste hauling;
- Benefit: We **PURCHASE BACK** all your compacted EPS;
- Environment Responsibility: Earn public relations points as a green business;
- Ease of Use: Simple, Safe, One-person operation;
- Safe: Cold compression with no fumes and minimal electrical requirements.



> Technical Data

ITEM	C100
Total Power Consumption	9.55 KW / 12.80 HP
Dimensions	3900×650×1910 (l/w/h) mm 154×26×75 (l/w/h) in.
Shipping Dimensions	Main part: 2900×760×2200 (l/w/h) mm 114×30×87 (l/w/h) in. Output chute: 1400×500×700 (l/w/h) mm 55×20×28 (l/w/h) in.
Weight	1,200 kg / 2,650 lbs
Feed Hopper Door	800×500×1700 (l/w/h) mm / 31×20×67 (l/w/h) in.
EPS Block Dimensions	300×300(w/h) mm / 12×12(w/h) in.
Applicable Material	EPS (Styrofoam/expanded polystyrene)
Production Capacity	100 kg per hour / 220 lbs per hour
EPS Compression Ratio	50:1
Compressed EPS Density	200-400 kg/m ³ / 570-1140 lbs/cubic yard
Standard	UL/CSA

*Preferred Recycling Equipment Inc.
2 Main Street East. Box # 436
Grimsby, Ontario
L3M 4H8
Phone: 1.866.679.8783
Email: info@preferredrecyclingequipment.com
Web: www.preferredrecyclingequipment.com*