



**PREFERRED**  
Recycling Equipment Inc.

## **Poly Tank**



### Specifications:

#### STANDARD FLOOR SPECIFICATIONS:

3/8" HIGH MOLECULAR WEIGHT POLY  
3" STRUCTURAL CHANNEL CROSSMEMBERS, 12" ON CENTER  
1/1/2" HOOK THROUGH 3/4" PLATE  
1 1/2" AXLES WITH 4 HEAVY DUTY WHEELS  
2" X 6" X 1/4" UNDERCARRIAGE RAILS  
4" DIAMETER X 6" WIDE NOSE WHEELS WITH ZERKS  
8" DIAMETER X 10" REAR WHEELS  
UNIVERSAL CABLE LIFT HOOK  
SOLID STEEL BULLNOSE ON RAILS

#### STANDARD BODY SPECIFICATIONS:

3/8" HIGH MOLECULAR WEIGHT POLY - ALL INTERIOR WALLS  
3" X 4" X 7 GAUGE TOP RAILS  
5" X 3" X 12 GAUGE SIDE POSTS, 24" ON CENTER  
3" X 7" X 7 GAUGE REAR POSTS AT HINGE  
UP-LIFT LATCH RELEASE SYSTEM  
DOOR SEALS, FLEXIBLE NEOPRENE "E" SEAL  
TARP TIE DOWNS  
SEALED TAIL GATES ARE STANDARD ON POLY TANK CONTAINERS

#### TESTING:

ALL POLY TANK CONTAINERS ARE WATER TESTED AT FACTORY  
AS "WATERTIGHT"

#### OPTIONS AVAILABLE:

SMALL OR LARGE HOOK LIFT, COMBO - CABLE & HOOK LIFT,  
HEIL, DEMPSTER. CUSTOM HATCHES, PIPE FITTINGS, AND LIDS PER  
CUSTOMER SPECIFICATIONS. SIDE-SWING TAILGATE,  
A CUSTOM CREATION OF THE CUSTOMER'S CHOICE.

Preferred Recycling Equipment Inc.  
2 Main Street East. Box # 436  
Grimsby, Ontario  
L3M 4H8  
Phone: 1.866.679.8783  
Email: [info@preferredrecyclingequipment.com](mailto:info@preferredrecyclingequipment.com)  
Web: [www.preferredrecyclingequipment.com](http://www.preferredrecyclingequipment.com)